






Features

- 1/4" SONY HQ1 CCD
- Up to 570 Lines of resolution
- 0.7 lux/F1.8 (Color), 0.02 lux/F1.8 (B/W)
- 100x Zoom (10x Optical, 10x Digital)
- Day and Night Function
- Built-in On-Screen-Display
- Support Multi-Protocol Pelco D, Pelco P and more
- RS485 Communication bus
- 160 Programmable presets

Specifications

Image Sensor	Size	1/4" Inter Line Transfer CCD (HQ1)
	Total Pixels	811(H) x 508(V)
	Effective Pixels	768(H) x 494(V)
Optics	Lens	10x, f=3.8 to 38.0mm (F1.8)
	Min. Focus Distance	1000mm
	Digital Zoom	On/Off 2x - 10x
	Field of view	H: Appr. 51.2°(Wide), 5.58°(Tele) V: Appr. 39.3°(Wide), 4.27°(Tele)
SYNC.	Scanning System	2:1 Interlace
	Synchronization	Internal/VD-Lock
	Frequency	H:15.734KHz/V:59.94KHz
Electrical	Resolution	500TV Lines Color, 570TV Lines B/W
	Min. Illumination	0.7lux Color, 0.02lux B/W
	S/N	more than 50dB (AGC off)
	Focus	Auto/Manual/One Push
	Zoom Movement Speed	1.67sec: Wide to Tele
	IRIS Control	Auto/Manual
	Camera Title	On/Off (Display 15 characters)
	Camera ID	255 ID Selectable
	Day & Night	Auto 1, Auto 2, Color, B/W(IR Cut)
	Gain Control	Normal, High, Off
	White Balance	ATW/AWC/Manual
	BLC	Low/Middle/High/Off
	Electronic Shutter Speed	Auto (1/60~1/120,000sec)
	O.S.D.	Built-in
	Motion Detection	On/Off
	SSNR	Low/Middle/High
Privacy Masking	On/Off (32 zones)	



Wall Mount
Bracket Included



ISO
Certified

Specification subject to change without notice.