

H.264 4 Channel Mobile DVR



Features

- 4-channel inputs / 1-channel outputs
- Net transmitting: H. 264 Compression for IE,
- Support TCP/IP, UDP, DHCP
- Multiple playback modes: Normal play, fast forward, fast rewind, frame by frame
- Backup file via USB flash, USB disk, Network & SD



Specification

Video Compression	H.264	HDD Interface	Support 2.5 inch SATA HDD
Video System	NTSC / PAL	Network Interface	RJ45 Ethernet
Operation System	Linux	Network Protocol	Support TCP/IP, UDP, DHCP
Video Input / Output	4-channel inputs / 1-channel outputs	Network Function	Support to live view with IE (Internet Explorer)
Audio Compression	8kHz*16bit ADPCM	USB 2.0	USB disk (backup, system upgrade)
Audio Input / Output	4-channel inputs / 1-channel outputs	Playback Mode	Normal play, fast forward, fast rewind, frame by frame
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps	Back Up	Backup file via USB flash, USB disk, Network & SD
Playback Resolution	PAL: CIF(352x288), HD1(704x288), D1(704x576) NTSC: CIF(352x240), HD1(704x240), D1(704x480)	Total Recording Frame Rate	PAL: 25fps@D1, 50fps@HD1, 100fps@CIF NTSC: 30fps@D1, 60fps@HD1, 120fps@CIF
Recording Mode	Always / schedule / motion detection / sensor triggered	Delay recording time range	1min,5min,10min,20min,30min,40min,50min,60min
Recording Pack Time	15/30/45/60mins selectable	Alarm Mode	Motion Detection, Sensor triggered, video loss, HDD error, HDD full
Senor & Alarm I/O	4 sensor inputs / 2 alarm output	Operation Temperature	32°F to +104°F
Power Supply	DC 9-32V	Working Humidity	10% to 90%
Power Consumption	10-15W	Dimension	218mm(L)X 209mm(W)X 71mm(H)